peters rubber & plastics bv

TECHNICAL GUIDANCE



Hose installation guidelines

WRONG	RIGHT	
		Do not coil or uncoil hoses by twisting, kinking and pulling. Uncoil the hose by letting the coil spin freely until the hose is fully uncoiled. Reverse to coil the hose.
		Do not coil or uncoil hoses by twisting, kinking and pulling. Uncoil the hose by letting the coil spin freely until the hose is fully uncoiled. Reverse to coil the hose.
		Prevent the hose from kinking behind the fittings. Leave a straight length of 3-5x inner diameter begin the fittings.
		Prevent the hose from kinking behind the fittings and overbending beyond the hose's bending radius. Use angled fittings to prevent this.
		Prevent the hose from kinking behind the fittings and overbending beyond the hose's bending radius. Use angled fittings to prevent this.
		Prevent the hose from kinking behind the fittings and overbending beyond the hose's bending radius. Use angled fittings to prevent this.
		Prevent the hose from kinking behind the fittings and overbending beyond the hose's bending radius. Use angled fittings to prevent this.

peters rubber & plastics bv

TECHNICAL GUIDANCE

Hose installation guidelines

WRONG	RIGHT	
		While lifting or handling hoses while not installed, do not use rope or thin sling as support. Use appropriate tools like broad slings and preferably made for purpose hose lifters (hose buns).
		Avoid axial loads on the hose. Use angled or bent fittings.
		Prevent torsion when installing hoses. Use swiveled ends or intermediate swivels to prevent this.