



Tricoflex®

Premium PVC waterslang Geschikt voor professionele irrigatie en reiniging in de agrarische sector, bouwsector, tuinbouw, landschapsarchitectuur en in de landbouw - Dé kwaliteitsnorm voor professionele waterslangen - Zeer slijtvaste en UV-bestendige buitenwand - Zeer goede druk- en vormstabiliteit - Uiterst knikbestendig en torsievrij			Premium PVC Wasserschlauch Geeignet für professionelle Bewässerung und Reinigung in der Agrarindustrie, Bauindustrie, Garten- und Landschaftsbau und in der Landwirtschaft - Der Qualitätsstandard für professionelle Wasserschläuche - Hoch abriebfeste und UV beständige Decke - Sehr gute Druck- und Formstabilität - Hoch Knickfest und drallfrei			Premium PVC Water Hose Suitable for professional irrigation and cleaning in the agricultural industry, construction, gardening, landscaping and agriculture - The quality standard for professional water hoses - Highly abrasion-resistant and UV-resistant cover - Excellent pressure and dimensional stability - Highly kink-resistant and torsion-free		
Materiaal binnen: PVC Kleur inwendig: Zwart Materiaal buiten: PVC Kleur uitwendig: Geel Inlagen: Textiel inlagen			Material Seele: PVC Farbe Seele: Schwarz Material Decke: PVC Farbe Decke: Gelb Einlagen: Textileinlagen			Material tube: PVC Colour tube: Black Material cover: PVC Colour cover: Yellow Reinforcements: Textile reinforcements		
- Gebreide textielinlage in 5-laagse constructie - Tricoflex Soft & Flex technologie met TNT (Tricoflex Non Torsion) gebreide versterking			- Gestrickte Trikoteinlage in 5-Lagen Konstruktion - Tricoflex Soft & Flex Technologie mit TNT (Tricoflex Non Torsion) Trikot-Gewebe			- Knitted fabric insert in 5-layer construction - Tricoflex Soft & Flex technology with TNT (Tricoflex Non Torsion) knitted reinforcement		
Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar	Temperatuur Temperatur Temperature Min. -15 °C Max. 60 °C Werkdruk Betriebsdruck Working pressure Min. 8 bar Max. 10 bar Barstdruk Platzdruck Burst pressure Min. 20 bar Max. 25 bar		
12.5	17.6	125	0	150	10			
15	20.5	135	0	200	10			
19	25.3	180	0	270	9			
25	32.3	240	0	420	8			
30	39	300	0	620	8			
35	45	350	0	800	8			
40	51	400	0	1000	8			
50	63	500	0	1470	8			

