NR Spray

Hoogwaardige universele verfspuitslang

Geschikt voor verven, lakken, oplosmiddelen, verdunners, lucht, water, oliën en smeervetten

- Inwendig nylon, glad en naadloos voor optimale doorstroming
- Uitwendig zwart, glad en olie- en chemicaliënbestendig
- Gevlochten textielinlage

Materiaal binnen: NYLON
Kleur inwendig: Transparant
Materiaal buiten: NBR
Kleur uitwendig: Zwart
Inlagen: Textiel inlagen

- Siliconen / LABS vrije productie

Hochwertiger Farbspritzschlauch

Geeignet für Farben, Lacke, Lösungsmittel, Verdünner, Luft, Wasser, Öle, Schmierstoffe

- Nahtlose Nylonseele für optimale Strömungsverhältnisse
- Schwarze, glatte, Öl- und Chemikalienbeständige Decke
- Geflochtene Textileinlagen

Material Seele: NYLON
Farbe Seele: Transparent
Material Decke: NBR
Farbe Decke: Schwarz
Einlagen: Textileinlagen

- Silikon / LABS freie Produktion

Premium multi-purpose paintspray hose

Suitable for paints, varnish, solvents, thinners, air, water, oils and petrochemicals

- Seamless nylon tube with minimum friction loss ensures optimal flow
- Black, smooth, oil and chemical resistant cover
- Textile braided reinforcements

Material tube: NYLON
Colour tube: Transparent
Material cover: NBR
Colour cover: Black
Reinforcements: Textile reinforcements

- Silicone / LABS free production

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
6.4	12.4	48	0	120	52
9.5	17.8	64	0	220	52
12.7	22.1	104	0	330	52
19.1	30.2	152	0	540	52
25.4	38.4	199	0	800	52

Temperatuur | Temperatur | Temperature
Min. -18 °C | Max. 88 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 52 bar | Max. 52 bar

Barstdruk | Platzdruck | Burst pressure
Min. 208 bar | Max. 208 bar



Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice