



MFSD 8707®

Levensmiddelenbestendige zuig- en persslang <i>EG (EU) 1935:2004</i> <i>EG (EU) 2023:2006</i> <i>FDA (CFR 21 §177.2600)</i> Geschikt voor zuivel- en melkproducten, vruchtensap en vetrijke levensmiddelen - Zeer flexibel en knikvast - Elektrisch geleidend middels antistatische draad	Lebensmittelechter Saug- und Druckschlauch <i>EG (EU) 1935:2004</i> <i>EG (EU) 2023:2006</i> <i>FDA (CFR 21 §177.2600)</i> Geeignet für Milchprodukte, Fruchtsäfte und fettfreie Lebensmittel - Sehr flexibel und knickfest - Elektrisch leitfähig mittels Kupferlitze	Food grade suction and delivery hose <i>EG (EU) 1935:2004</i> <i>EG (EU) 2023:2006</i> <i>FDA (CFR 21 §177.2600)</i> Suitable for milk products, juices and fat free food products - Very flexible and kink resistant - Electrically conductive through antistatic wire
Materiaal binnen: NR Kleur inwendig: Wit Materiaal buiten: EPDM Kleur uitwendig: Blauw Inlagen: Textiel inlagen + stalen spiraal	Material Seele: NR Farbe Seele: Weiß Material Decke: EPDM Farbe Decke: Blau Einlagen: Textileinlagen + Stahlspirale	Material tube: NR Colour tube: White Material cover: EPDM Colour cover: Blue Reinforcements: Textile reinforcements + steel spiral
- Reinigingstemperatuur max. 110 °C kortstondig	- Steriliseerbaar bis max. 110 °C kurzzeitig	- Sterilizing temperature max. 110 °C intermittend

Binnen Innen Inside Ø mm	Buiten Aussen Outside Ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
13	23	130	0	418	10
19	29	190	0	537	10
19	30	190	0	599	10
25	36	250	0	726	10
32	43	320	0	937	10
32	54	320	0	1947	10
38	51	380	0	1338	10
40	52	400	0	1310	10
45	58	450	0	1570	10
50	63	500	0	1647	10
51	64	510	0	1630	10
51	65	510	0	1843	10
55	68	550	0	1814	10
63	77	630	0	2277	10
63	78	630	0	2469	10
75	90	750	0	2923	10
76	91	760	0	2910	10
76	92	760	0	2965	10
90	105	900	0	3413	10
90	106	900	0	3645	10
100	118	1000	0	4773	10
102	118	1020	0	4420	10
102	120	1020	0	4944	10

Geleiding | Leitfähigkeit | Conductivity

Normeringen | Normen | Standards
 FDA 177:2600 | EG 1935/2004

Temperatuur | Temperatur | Temperature
 Min. -30 °C | Max. 80 °C

Werkdruk | Betriebsdruck | Working pressure
 Min. 10 bar | Max. 10 bar

Barstdruk | Platzdruck | Burst pressure
 Min. 30 bar | Max. 30 bar

