Airbrake SAE J1402

Remslang volgens SAE J1402A

Geschikt voor luchtremsystemen en andere pneumatische systemen in voertuigen en trailers

- Overtreft SAE J1402 specificaties
- Gladde, oliebestendige buitenwand
- Zeer soepel, flexibel en knikvast

Materiaal binnen:	EPDM
Kleur inwendig:	Zwart
Materiaal buiten:	EPDM
Kleur uitwendig:	Zwart
Inlagen	Textiel inlagen

- Conform D.O.T. (Department of Transportation) FMVSS 106
- 100% druktest in de fabriek

Bremsschlauch nach SAE J1402A

Geeignet für Druckluftbremsanlagen und sonstige Druckluftanlagen in Kraftfahrzeugen, sowie Anhängerfahrzeugen

- Übertrifft in Leistungsdaten SAE J1402
- Glatte, ölbeständige Decke
- Hochflexibel und knickfest

Material Seele:	EPDM
Farbe Seele:	Schwarz
Material Decke:	EPDM
Farbe Decke:	Schwarz
Einlagen:	Textiel inlagen

- Entspricht D.O.T. (Department of Transportation) FMVSS 106
- 100% druckgeprüft in der Fabrik

Airbrake hose according SAE J1402A

Suitable for air brake systems and other pneumatic systems in vehicles and trailers

- Exceeds SAE J1402 requirements
- Smooth, oil resistant cover
- Excellent kink and torsion resistance

Material tube:	EPDM
Colour tube:	Black
Material cover:	EPDM
Colour cover:	Black
Reinforcements:	Textiel inlagen

- Meets D.O.T. (Department of Transportation) FMVSS 106
- 100% factory pressure tested

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
9.5	19.5	80	0	250	10
12.5	22.5	105	0	350	10

Normeringen | Normen | Standards
SAE J 1402 / D.O.T. FMVSS 106

Temperatuur | Temperatur | Temperature
Min. -40 °C | Max. 100 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 10 bar | Max. 10 bar

Barstdruk | Platzdruck | Burst pressure
Min. 90 bar | Max. 90 bar

Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice