



Super Tress-Nobel® 80 bar

Hogedruk PVC slang			Hochdruck PVC Schlauch			High pressure PVC hose		
Geschikt voor landbouwspruiten (80 Bar), water, perslucht, vloeibare meststoffen, insecticiden en pesticiden			Geeignet für landwirtschaftliche Spritzmittel (80 Bar), Wasser, Druckluft, Flüssigdünger, Insektizide und Pestizide			Suitable for agricultural spraying (80 Bar), water, compressed air, fluid fertilizers, insecticides and pesticides		
- Zeer flexibel en knikbestendig - Minimaal drukverlies - Hoge UV- en weersbestendigheid			- - Hochflexibel und knickfest - - Minimaler Druckverlust - - Hohe UV- und Witterungsbeständigkeit			- Highly flexible and kink resistant - Low friction pressure loss - High UV and weather resistance		
Materiaal binnen: PVC Kleur inwendig: Zwart Materiaal buiten: PVC Kleur uitwendig: Blauw Inlagen: Textiel inlagen			Material Seele: PVC Farbe Seele: Schwarz Material Decke: PVC Farbe Decke: Blau Einlagen: Textileinlagen			Material tube: PVC Colour tube: Black Material cover: PVC Colour cover: Blue Reinforcements: Textile reinforcements		
- Met gevlochten polyesterinlagen voor minimale lengterek en hoge weerstand tegen drukstoten			- Mit gekreuzte Polyestereinlagen für minimale Längsdehnung und hohen Widerstand gegen Druckstöße			- With braided polyester reinforcements for low elongation and high resistance against pressure surges		
Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar	Temperatuur Temperatur Temperature Min. -15 °C Max. 60 °C		
10	19	70	0	273	80	Werkdruk Betriebsdruck Working pressure Min. 80 bar Max. 80 bar		
12	22	84	0	356	80			
19	30.5	153	0	581	80	Barstdruk Platzdruck Burst pressure Min. 240 bar Max. 240 bar		

