



8024 Food Flow BfR

<p>Voedingsmiddelen persslang <i>EG (EU) 1935/2004</i> <i>EG (EU) 2023/2006</i> <i>BfR XXI:2002 (Cat. 2)</i></p> <p>Geschikt voor olie- en vethoudende producten, bier, wijn, vruchtensap en melkproducten</p> <ul style="list-style-type: none"> - Zeer flexibel en knikvast - Reinigen conform 3A class II standaard - Heet water max. 6 bar tot 80 °C 	<p>Lebensmittelechter Druckschlauch <i>EG (EU) 1935/2004</i> <i>EG (EU) 2023/2006</i> <i>BfR XXI:2002 (Kat. 2)</i></p> <p>Geeignet für öl - und fetthaltige Lebensmittel, Bier, Wein, Fruchtsäfte und Milchprodukte</p> <ul style="list-style-type: none"> - Hoch flexibel und knickfest - Reinigung entspr. 3A Class II Norm - Heißwasser max. 6 bar bis zu 80 °C 	<p>Food delivery hose <i>EG (EU) 1935/2004</i> <i>EG (EU) 2023/2006</i> <i>BfR XXI:2002 (Cat. 2)</i></p> <p>Suitable for fatty and oily food products, beer, wine, fruit juices and dairy products</p> <ul style="list-style-type: none"> - Very flexible and kink resistant - Cleaning according to 3A class II standard - Hot water max. 6 bar up to 80 °C
<p>Materiaal binnen: NBR Kleur inwendig: Wit Materiaal buiten: NBR/PVC Kleur uitwendig: Blauw Inlagen: PVA inlagen</p>	<p>Material Seele: NBR Farbe Seele: Weiß Material Decke: NBR/PVC Farbe Decke: Blau Einlagen: PVA-Einlagen</p>	<p>Material tube: NBR Colour tube: White Material cover: NBR/PVC Colour cover: Blue Reinforcements: PVA reinforcements</p>
<ul style="list-style-type: none"> - Naadloos geëxtrudeerde binnen- en buitenwand - Binnen- en buitenwand bestand tegen eetbare en dierlijke oliën 	<ul style="list-style-type: none"> - Nahtlos extrudierte Seele und Decke - Seele und Decke beständig gegen pflanzliche und tierische Öle 	<ul style="list-style-type: none"> - Seamless extruded tube and cover - Tube and cover resistant to vegetable and animal oils

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
9.5	18.5	74	0	262	20
12.7	21.6	86	0	317	20
15.9	25.1	100	0	392	20
19.1	28.6	114	0	469	20
25.4	35.6	142	0	645	20

Normeringen | Normen | Standards
 EG 1935/2004 | EG 2023/2006 | BFR XXI CAT.2

Temperatuur | Temperatur | Temperature
 Min. -20 °C | Max. 100 °C

Werkdruk | Betriebsdruck | Working pressure
 Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
 Min. 60 bar | Max. 60 bar

