# Unicord®

**Universele EPDM slang met zes oranje strepen**

Geschikt voor (heet) water, lucht, lichte zuren en chemicaliën, reinigingsmiddelen, koelvloeistoffen, zoutoplossingen en zeewater

- Zeer flexibel en knikvast
- Vrij van halogenen

**Materiaal binnen:** EPDM
**Kleur inwendig:** Zwart
**Materiaal buiten:** EPDM
**Kleur uitwendig:** Zwart
**Inlagen:** Textiel inlagen

- Geproduceerd in EU

**EPDM Vielzweckschlauch mit sechs orangen Kennstreifen**

Geeignet als Deckwaschschlauch, Kühlmittel, Heißwasser, Reinigungsmittel, Chemikalien und Reinigungsmittel

- Sehr geschmeidige und knickfeste Ausführung
- Halogenfrei hergestellt

**Material Seele:** EPDM
**Farbe Seele:** Schwarz
**Material Decke:** EPDM
**Farbe Decke:** Schwarz
**Einlagen:** Textileinlagen

- Made in EU

**Multi-purpose EPDM hose with six orange stripes**

Suitable as wash down hose, (hot) water, light acids and chemicals, cleaning products, cooling agents, salt solutions and seawater

- Extremely flexible and kink resistant
- Halogene free

**Material tube:** EPDM
**Colour tube:** Black
**Material cover:** EPDM
**Colour cover:** Black
**Reinforcements:** Textile reinforcements

- Made in EU

| Binnen<br>Innen<br>Inside<br>ø mm | Buiten<br>Aussen<br>Outside<br>ø mm | Buigstr.<br>Biegerad.<br>Bendrad.<br>mm | Vacuüm<br>Vakuum<br>Vacuum<br>Bar | Gewicht<br>Gewicht<br>Weight<br>gr/m | Werkdruk<br>Betriebsdruck<br>Work. press.<br>Bar |
|---|---|---|---|---|---|
| 13 | 20 | 78 | 0 | 305 | 15 |
| 19 | 27 | 100 | 0 | 360 | 15 |
| 25 | 34 | 150 | 0 | 410 | 15 |

**Temperatuur | Temperatur | Temperature**
Min. -40 °C | Max. 100 °C

**Werkdruk | Betriebsdruck | Working pressure**
Min. 15 bar | Max. 15 bar

**Barstdruk | Platzdruck | Burst pressure**
Min. 45 bar | Max. 45 bar





Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice