



Radiator 3

Rubber radiateurslang Geschikt voor koelvloeistoffen en heet water tot 100 °C - Uitwendig met doekafdruk - Per meter gemerkt met inwendige diameter		Gummi Kühlerschlauch Geeignet für Kühlflüssigkeiten und Heißwasser bis 100 °C - Außen stoffgemustert - Angabe des Innendurchmessers je Meter		Rubber radiator hose Suitable for common cooling fluids and hot water up to 100 °C - Cover with fabric pattern - Each meter with bore size indication	
Materiaal binnen: Kleur inwendig: Materiaal buiten: Kleur uitwendig: Inlagen	EPDM Zwart EPDM Zwart Textiel inlagen	Material Seele: Farbe Seele: Material Decke: Farbe Decke: Einlagen:	EPDM Schwarz EPDM Schwarz Textiel inlagen	Material tube: Colour tube: Material cover: Colour cover: Reinforcements:	EPDM Black EPDM Black Textiel inlagen

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
12	18	120	0	195	3
13	19	130	0	221	3
15	22	150	0	282	3
16	23	160	0	305	3
18	25	180	0	328	3
19	26	190	0	343	3
20	27	200	0	358	3
22	29	220	0	389	3
25	32	250	0	441	3
28	35	280	0	441	3
30	38	300	0	595	3
32	40	320	0	626	3
35	43	350	0	682	3
38	46	380	0	734	3
40	48	400	0	769	3
42	50	420	0	804	3
45	53	450	0	909	3
48	56	480	0	919	3
51	51	510	0	1226	3
55	65	550	0	1318	3
57	67	570	0	1362	3
60	70	600	0	1428	3
63	73	630	0	1439	3
65	75	650	0	1538	3
70	80	700	0	1648	3
75	85	750	0	1757	3

Normeringen | Normen | Standards
ISO 1307

Temperatuur | Temperatur | Temperature
Min. -40 °C | Max. 120 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 3 bar | Max. 3 bar

Barstdruk | Platzdruck | Burst pressure
Min. 9 bar | Max. 9 bar

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
80	92	800	0	2248	3
90	102	900	0	2579	3
102	114	1020	0	2916	3
110	122	1100	0	3116	3
114	126	1140	0	3251	3
120	132	1200	0	3241	3
127	139	1280	0	3421	3
140	152	1440	0	3755	3
159	173	1510	0	5014	3
168	180	1580	0	4539	3



2026

flexati
H O S E