

Unicord®

Universele EPDM slang met zes oranje strepen

Geschikt voor (heet) water, lucht, lichte zuren en chemicaliën, reinigingsmiddelen, koelvloeistoffen, zoutoplossingen en zeewater

- Zeer flexibel en knikvast
- Vrij van halogenen

Materiaal binnen: EPDM
Kleur inwendig: Zwart
Materiaal buiten: EPDM
Kleur uitwendig: Zwart
Inlagen: Textiel inlagen

- Geproduceerd in EU

EPDM Vielzweckschlauch mit sechs orangen Kennstreifen

Geeignet als Deckwaschschlauch, Kühlmittel, Heißwasser, Reinigungsmittel, Chemikalien und Reinigungsmittel

- Sehr geschmeidige und knickfeste Ausführung
- Halogenfrei hergestellt

Material Seele: EPDM
Farbe Seele: Schwarz
Material Decke: EPDM
Farbe Decke: Schwarz
Einlagen: Textileinlagen

- Made in EU

Multi-purpose EPDM hose with six orange stripes

Suitable as wash down hose, (hot) water, light acids and chemicals, cleaning products, cooling agents, salt solutions and seawater

- Extremely flexible and kink resistant
- Halogene free

Material tube: EPDM
Colour tube: Black
Material cover: EPDM
Colour cover: Black
Reinforcements: Textile reinforcements


- Made in EU

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
13	20	78	0	305	15
19	27	100	0	360	15
25	34	150	0	410	15

Temperatuur | Temperatur | Temperature
Min. -40 °C | Max. 100 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 15 bar | Max. 15 bar

Barstdruk | Platzdruck | Burst pressure
Min. 45 bar | Max. 45 bar



Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice