Heliflex SL

Groen transparante PVC zuigslang

Geschikt voor afzuigen van water, vuilwater, water met lichte aandelen van vaste stoffen

- Zeer gladde binnenwand voor optimale flow
- Voorzien van witte, slagvaste extra stevige spiraal
- Zeer flexibel en knikvast

Materiaal binnen:	PVC
Kleur inwendig:	Groen transparant
Materiaal buiten:	PVC
Kleur uitwendig:	Groen transparant
Inlagen:	PVC spiraal

Grüner transparenter PVC Saugschlauch

Geeignet zum Ansaugen von Wasser, Abwasser und Waser mit niedrigem Feststoffanteil

- Sehr glatte Innenseele für optimales Strömungsverhalten
- Mit schlag- und trittfester weißer Spirale
- Hoch flexibel und knickfest

Material Seele:	PVC
Farbe Seele:	Grün transparent
Material Decke:	PVC
Farbe Decke:	Grün transparent
Einlagen:	PVC-Spirale

Green transparent PVC suction hose

Suitable for suction of water, manure, wastewater, water with low solids content

- Smooth inner surface for optimized flow
- With shock resistant and crushproof white spiral
- Highly flexible and kink resistant

Material tube:	PVC
Colour tube:	Green transparent
Material cover:	PVC
Colour cover:	Green transparent
Reinforcements:	PVC spiral

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
20	23.8	125	0.6	230	7
25	29	125	0.6	250	7
32	36.6	160	0.6	290	5
38	44.6	200	0.6	480	5
40	46.2	210	0.6	470	5
45	52	225	0.6	640	5
50	56.8	250	0.6	680	5
60	67.4	300	0.6	850	5
63	70.4	315	0.6	315	4
75	83	375	0.6	1160	4
90	98.8	450	1430	1430	3
100	109.2	500	0.6	1850	3
152	164.4	800	0.6	3250	2.5

Temperatuur | Temperatur | Temperature
Min. -5 °C | Max. 55 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 2.5 bar | Max. 7 bar

Barstdruk | Platzdruck | Burst pressure
Min. 6.3 bar | Max. 17 bar

Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice