



Airform PLW 20

Rubber perslucht en waterslang Geschikt voor water, perslucht en algemene industriële toepassingen - In- en uitwendig glad - Flexibel en knikvast - Weerbestendige en slijtvaste buitenwand	Gummi Pressluft- und Wasserschlauch Geeignet für Luft, Wasser und allgemeine industrielle Einsatzzwecke - Innen und außen glatt - Flexibel - und knickfest - Abrieb- und witterungsbeständige Decke	Rubber compressed air and water hose Suitable for air, water and general industrial applications - Smooth tube and cover - Kink resistant and flexible - Abrasion and weather resistant cover
Materiaal binnen: SBR Kleur inwendig: Zwart Materiaal buiten: SBR Kleur uitwendig: Zwart Inlagen: Textiel inlagen	Material Seele: SBR Farbe Seele: Schwarz Material Decke: SBR Farbe Decke: Schwarz Einlagen: Textileinlagen	Material tube: SBR Colour tube: Black Material cover: SBR Colour cover: Black Reinforcements: Textile reinforcements
- Geproduceerd in EU	- Hergestellt in EU	- Made in EU

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
6	12	60	0	130	20
8	15	80	0	170	20
10	17	100	0	200	20
13	21	130	0	290	20
16	26	160	0	460	20
19	30	220	0	520	20
25	35	250	0	650	20

Temperatuur | Temperatur | Temperature
Min. -30 °C | Max. 70 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 20 bar | Max. 20 bar

Barstdruk | Platzdruck | Burst pressure
Min. 60 bar | Max. 60 bar

