

Primabel®

PVC waterslang

Geschikt voor irrigatie en reiniging in de agrarische sector, bouwsector, tuinbouw, landschapsarchitectuur en landbouw

- Flexibel en comfortabel in gebruik
- Uitstekende UV-bestendigheid
- Meerlaagse structuur

PVC Wasserschlauch

Geeignet für Bewässerung und Reinigung in der Agrarindustrie, Bauindustrie, Garten- und Landschaftsbau und in der Landwirtschaft

- Flexible und komfortable Handhabung
- Sehr gute UV-Beständigkeit
- Mehrschichtige Struktur

PVC water hose

Suitable for irrigation and cleaning in the agricultural industry, construction, gardening, landscaping, and agriculture

- Flexible and comfortable to use
- Excellent UV resistance
- Multi-layer structure

Materiaal binnen:	PVC
Kleur inwendig:	Zwart
Materiaal buiten:	PVC
Kleur uitwendig:	Geel
Inlagen:	Textiel inlagen

Material Seele:	PVC
Farbe Seele:	Schwarz
Material Decke:	PVC
Farbe Decke:	Gelb
Einlagen:	Textileinlagen

Material tube:	PVC
Colour tube:	Black
Material cover:	PVC
Colour cover:	Yellow
Reinforcements:	Textile reinforcements

- Gemaakt van 80% circulair gerecycled PVC uit fabriekseigen afvalstromen
- Gebreide textielinlage en 2-laagse, gladde binnenwand
- Tricoflex Soft & Flex technologie met TNT (Tricoflex Non Torsion) gebreide versterking

- Made from 80% circular recycled PVC from the factory's own waste streams
- Gestrickte Trikoteinlage in 5-Lagen Konstruktion
- Tricoflex Soft & Flex Technologie mit TNT (Tricoflex Non Torsion) Trikot-Gewebe

- Produces from 80% recycled PVC from factory's own waste streams
- Knitted fabric insert and 2-layer, smooth inner tube
- Tricoflex Soft & Flex technology with TNT (Tricoflex Non Torsion) knitted reinforcement

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
12.5	17	140	0	110	8
15	19.1	160	0	130	8
19	23.8	200	0	200	8
25	31	255	0	350	8
30	38.4	460	0	530	8

Temperatuur | Temperatur | Temperature
Min. -15 °C | Max. 60 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 8 bar | Max. 8 bar

Barstdruk | Platzdruck | Burst pressure
Min. 16 bar | Max. 20 bar



Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice