

Aqua Standard

Rood geribde rubber waterslang

Geschikt voor industrie, tuin- en landbouw

- Uitwendig rood breed geribd
- Zeer flexibel en knikvast
- Weer- en verouderingsbestendig

Materiaal binnen: SBR
Kleur inwendig: Zwart
Materiaal buiten: SBR/EPDM
Kleur uitwendig: Rood
Inlagen: Textiel inlagen

- Geproduceerd in EU

Rot geriefter Gummi Wasserschlauch

Geeignet für Garten, Kommunalbetriebe und Industrie

- Außen rot mit breiten Knickschutz riefen
- Hochflexibel, knickfest und drallfrei
- Witterungs- und alterungsbeständige Decke

Material Seele: SBR
Farbe Seele: Schwarz
Material Decke: SBR/EPDM
Farbe Decke: Rot
Einlagen: Textileinlagen

- Hergestellt in EU

Red ribbed rubber water hose

Suitable for gardening, agriculture and industry

- Cover with wide, red ribs
- Kink resistant and flexible
- Weather and ageing resistant cover

Material tube: SBR
Colour tube: Black
Material cover: SBR/EPDM
Colour cover: Red
Reinforcements: Textile reinforcements

- Made in EU

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
13	19.5	130	0	270	10
16	23	160	0	330	10
20	28	200	0	390	10
25	33	250	0	570	10

Temperatuur | Temperatur | Temperature
Min. -30 °C | Max. 70 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 10 bar | Max. 10 bar

Barstdruk | Platzdruck | Burst pressure
Min. 30 bar | Max. 30 bar



Technische wijzigingen voorbehouden, Techn. Änderungen möglich ohne vorige Ankündigung, Tech.data subject to change without prior notice