



Tricoflex®

Premium PVC waterslang

Geschikt voor professionele irrigatie en reiniging in de agrarische sector, bouwsector, tuinbouw, landschapsarchitectuur en in de landbouw

- Dé kwaliteitsnorm voor professionele waterslangen
- Zeer slijtvaste en UV-bestendige buitenwand
- Zeer goede druk- en vormstabiliteit
- Uiterst knikbestendig en torsievrij

Premium PVC Wasserschlauch

Geeignet für professionelle Bewässerung und Reinigung in der Agrarindustrie, Bauindustrie, Garten- und Landschaftsbau und in der Landwirtschaft

- Der Qualitätsstandard für professionelle Wasserschläuche
- Hoch abriebfeste und UV beständige Decke
- Sehr gute Druck- und Formstabilität
- Hoch Knickfest und drallfrei

Premium PVC Water Hose

Suitable for professional irrigation and cleaning in the agricultural industry, construction, gardening, landscaping and agriculture

- The quality standard for professional water hoses
- Highly abrasion-resistant and UV-resistant cover
- Excellent pressure and dimensional stability
- Highly kink-resistant and torsion-free

Materiaal binnen: PVC
Kleur inwendig: Zwart
Materiaal buiten: PVC
Kleur uitwendig: Geel
Inlagen: Textiel inlagen

Material Seele: PVC
Farbe Seele: Schwarz
Material Decke: PVC
Farbe Decke: Gelb
Einlagen: Textileinlagen

Material tube: PVC
Colour tube: Black
Material cover: PVC
Colour cover: Yellow
Reinforcements: Textile reinforcements

- Gebreide textielinlage in 5-laagse constructie
- Tricoflex Soft & Flex technologie met TNT (Tricoflex Non Torsion) gebreide versterking

- Gestrickte Trikoteinlage in 5-Lagen Konstruktion
- Tricoflex Soft & Flex Technologie mit TNT (Tricoflex Non Torsion) Trikot-Gewebe

- Knitted fabric insert in 5-layer construction
- Tricoflex Soft & Flex technology with TNT (Tricoflex Non Torsion) knitted reinforcement

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
12.5	17.6	125	0	150	10
15	20.5	135	0	200	10
19	25.3	180	0	270	9
25	32.3	240	0	420	8
30	39	300	0	620	8
35	45	350	0	800	8
40	51	400	0	1000	8
50	63	500	0	1470	8

Temperatuur | Temperatur | Temperature
Min. -15 °C | Max. 60 °C

Werkdruk | Betriebsdruck | Working pressure
Min. 8 bar | Max. 10 bar

Barstdruk | Platzdruck | Burst pressure
Min. 20 bar | Max. 25 bar

