



## Tress-Nobel® 40 bar

Inwendig Kleur Uitwendig Kleur	PVC Zwart PVC Blauw	Innen Farbe Außen Farbe	PVC Schwarz PVC Blau	Inside Colour Outside Colour	PVC Black PVC Blue
---	------------------------------	----------------------------------	-------------------------------	---------------------------------------	-----------------------------

### Hogedruk 4 lagen TPE slang

Geschikt voor water, lucht, meststoffen en bestrijdingsmiddelen

- Met kruislings gevlochten polyester inlagen
- Minimale lengterek en hoge weerstand tegen drukpieken
- Zeer flexibel en knikvast
- Minimaal drukverlies
- Zeer goed bestand tegen UV en weersinvloeden

Tevens leverbaar uitwendig zwart

### Hochdruck 4 Lagen TPE Schlauch

Geeignet für Wasser, Luft, Düngemittel und Schädlingsbekämpfungsmittel

- Mit gekreuzte Polyestereinlagen
- Minimale Längsdehnung und hohen Widerstand gegen Druckstöße
- Hoch flexibel und knickfest
- Minimaler Druckverlust
- Hohe UV und Ozonbeständigkeit

Ebenfalls lieferbar mit schwarzer Decke

### High pressure 4 ply TPE hose

Suitable for air, water, chemicals, fluid fertilizers and pesticide

- With braided polyester reinforcements for low elongation and high resistance against pressure surges
- Highly flexible and kink resistant
- Low friction pressure loss
- Also available with blue cover
- High UV and ozone resistance

also available with black cover

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
6.3	12.5	44	0	112	40
8.0	14.5	56	0	151	40
9.0	16.0	63	0	181	40
10.0	17.0	70	0	195	40
12.0	20.0	84	0	264	40
16.0	24.0	112	0	331	40
19.0	28.0	145	0	437	40
25.0	35.0	210	0	622	40

Normen / Standards  
ISO R 1307

Temperatuurbereik (Zie medium)  
Temperatuurbereik (siehe Medium)  
Temperature range (see media)  
-15 °C +60 °C

Werkdruk Betriebsdruck Working pressure 40 bar	Barstdruk Platzdruck Burst pressure 120 bar
---	--

Markering / Markierung / Branding:  
TRESS-NOBEL 40 BAR [BATCH NUMBER]

Lengten / Längen / Lengths  
25 / 50 / 100 m

Kan per diameter verschillen / Kann je nach Durchmesser variieren / Can vary per diameter



-2025-

