



Primabel®

Inwendig Kleur Uitwendig Kleur	PVC Zwart PVC Geel	Innen Farbe Außen Farbe	PVC Schwarz PVC Gelb	Inside Colour Outside Colour	PVC Black PVC Yellow
---	-----------------------------	----------------------------------	-------------------------------	---------------------------------------	-------------------------------

<p>5 lagige kwaliteitswaterslang</p> <ul style="list-style-type: none"> - Soepele, gladde binnenwand - UV bestendige en kleurvaste buitenwand - Druk en torsiebestendige inlagen - Met gebreide inlagen - Gemaakt van 70% circulair PVC uit eigen afvalstromen uit de fabriek <p>Leverbaar in geel (type 900) en groen opaak (type 950)</p>	<p>5 Lagen Qualitätswasserschlauch</p> <ul style="list-style-type: none"> - UV beständige, farbechte Decke - Mit gestrickter Trikot einlage - Druck und verwindungsfeste Einlagen - Hoch flexibel und knickfest - Hergestellt aus 70 % zirkulärem PVC aus werkseigenen Abfallströmen <p>Lieferbar in gelb (Typ 900) und grün opak (Typ 950)</p>	<p>9 ply quality water hose</p> <ul style="list-style-type: none"> - UV resistant, non fading cover - With knitted inserts and foam layers - Highly flexible and kink resistant - Pressure and torsion resistant inserts - Made from 70% circular PVC from the factory's own waste streams <p>Available in yellow (type 900) or green opaque (type 950)</p>
--	--	--

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
12.5	17.0	140.0	0	110	8
15.0	19.1	160.0	0	130	8
19.0	23.8	200.0	0	200	6
25.0	31.0	255.0	0	350	6
30.0	38.4	460.0	0	530	6

Normen / Standards

Temperatuurbereik (Zie medium)
Temperatuurbereich (siehe Medium)
Temperature range (see media)
-15 °C +60 °C

Werkdruk Betriebsdruck Working pressure 8 - 6 bar	Barstdruk Platzdruck Burst pressure 20 - 16 bar
--	--

Markering / Markierung / Branding:
PRIMABEL SOFT & FLEX TECHNOLOGY
[BATCH NUMBER]

Lengten / Längen / Lengths
25 / 50 m

Kan per diameter verschillen / Kann je nach Durchmesser variieren / Can vary per diameter



-2025-

