



## Tricoclair® AL

Inwendig Kleur Uitwendig Kleur	PVC Transparant PVC Transparant	Innen Farbe Außen Farbe	PVC Transparent PVC Transparent	Inside Colour Outside Colour	PVC Transparent PVC Transparent
Topkwaliteit 3 lagen PVC levensmiddelen slang		Spitzenqualität 3 Lagen PVC Lebensmittelschlauch		Top grade 3 ply PVC food hose	
Geschikt voor perslucht, industriële gassen, levensmiddelen en chemicaliën		Geeignet für Pressluft, Wasser, Industriegase, Chemikalien und Lebensmittel		Suitable for air, water, chemicals, food products and industrial gas	
<ul style="list-style-type: none"> <li>- Met polyester inlagen</li> <li>- Zeer soepel en knikvast</li> <li>- Minimaal drukverlies</li> <li>- Hoge vakuumbestendigheid t/m ø 25 mm</li> <li>- DEHP vrije compound conform EC 10/2011/CE</li> <li>- Glas/vork symbol</li> </ul>		<ul style="list-style-type: none"> <li>- Mit Polyesterinlagen</li> <li>- Sehr geschmeidig und knickfest</li> <li>- Minimaler Druckverlust</li> <li>- Gute Vakuumbeständigkeit bis ø 25mm</li> <li>- DEHP frei entsprechend Richtlinie EC 10/2011/CE</li> <li>- Glas/Gabel Symbol</li> </ul>		<ul style="list-style-type: none"> <li>- With polyester reinforcements</li> <li>- Souple and kink resistant</li> <li>- Minimal pressure friction loss</li> <li>- Good vacuum resistance up to ø 25 mm</li> <li>- DEHP free compound according to directive EC 10/2011/CE</li> <li>- Glass/fork symbol</li> </ul>	

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
4.0	8.0	22.0	0	45	27
4.0	10.0	32.0	0	80	22
6.0	12.0	36.0	0	102	22
7.0	13.0	46.0	0	108	21
8.0	14.0	54.0	0	127	20
9.0	15.0	66.0	0	135	20
10.0	16.0	74.0	0	146	20
12.0	19.0	90.0	0	204	20
13.0	20.0	101.0	0	218	20
15.0	23.0	120.0	0	291	20
19.0	27.0	157.0	0	346	20
25.0	34.0	219.0	0	500	16
25.0	36.0	225.0	0	631	17
30.0	41.0	277.0	0	748	13
32.0	42.0	320.0	0	697	12
38.0	48.0	420.0	0	810	12
40.0	52.0	460.0	0	1040	10
50.0	64.0	600.0	0	1467	9

Normen / Standards  
EC 10/2011 - EC 1935

Temperatuurbereik (Zie medium)  
Temperatuurbereich (siehe Medium)  
Temperature range (see media)  
-15 °C +60 °C

Werkdruk	Barstdruk
Betriebsdruck	Platzdruck
Working pressure	Burst pressure
9 - 27 bar	28 - 81 bar

Markering / Markierung / Branding:  
TRICOCLAIR AL Ø INN X Ø OUT / Ø INN X TH.  
GLASS/FORK SYMBOL (EU) NO 10/2011 [WP]  
BAR [BATCH NUMBER]

Lengten / Längen / Lengths  
25 / 50 / 100 m  
Kan per diameter verschillen / Kann je nach  
Durchmesser variieren / Can vary per  
diameter



-2024-

