



Beton 40

Inwendig Kleur Uitwendig Kleur	NR/SBR Zwart SBR Zwart	Innen Farbe Außen Farbe	NR/SBR Schwarz SBR Schwarz	Inside Colour Outside Colour	NR/SBR Black SBR Black
---	---------------------------------	----------------------------------	-------------------------------------	---------------------------------------	---------------------------------

Betonmortelslang - Zeer slijtvaste binnenwand - Textielcoordinlagen voor minimale lengterek onder druk - Knikvast en flexibel Gekenmerkt overeenkomstig Duitse BG veiligheidsvoorschriften	Mörtelförderschlauch - Hoch abriebfeste Innenseele - Textilcordeinlagen für minimale Längsdehnung unter Druck - Knickfest und drallfrei Kennzeichnung gemäß Berufsgenossenschaftlicher Vorschriften	Concrete placement hose - High abrasion resistant tube and cover - Synthetic cord plies for minimal elongation under working pressure - Excellent torsion and kink resistance Conforms to German BG safety standards
--	---	--

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
19.0	32.0	150.0	0	615	40
25.0	39.0	200.0	0	780	40
32.0	46.0	250.0	0	1030	40
35.0	49.0	275.0	0	1195	40
38.0	54.0	300.0	0	1360	40
40.0	54.0	320.0	0	1400	40
45.0	59.0	360.0	0	1570	40
50.0	68.0	410.0	0	1800	40
63.0	83.0	480.0	0	2360	40

Normen / Standards

Temperatuurbereik (Zie medium)
Temperatuurbereik (siehe Medium)
Temperature range (see media)
-30 °C +70 °C

Werkdruk	Barstdruk
Betriebsdruck	Platzdruck
Working pressure	Burst pressure
40 bar	120 bar

Markering / Markierung / Branding:
BETON /40 WP 40 BAR DIA

Lengten / Längen / Lengths

40 m
Kan per diameter verschillen / Kann je nach Durchmesser variieren / Can vary per diameter