



PUR XL

Inwendig Kleur Uitwendig Kleur	PU Bruin transparant VERKOPERDE SPIRAAL Bruin transparant	Innen Farbe Außen Farbe	PU Braun transparent FEDERSTAHL VERKUPFERT Braun transparent	Inside Colour Outside Colour	PU Brown Transparent COPPER PLATED SPIRAL Brown Transparent
---	--	----------------------------------	---	---------------------------------------	--

PU Ester zuigslang	PU Ester Spiralschlauch	PU Ester suction hose
Geschikt voor zware toepassingen	Geeignet für schwere Anforderungen	Suitable for heavy duty applications
- Met verkoperde en vast ingegoten spiraal - Wanddikte ca. 2,5 mm - Optimaal stromingsprofiel - Antistatisch [R<10GΩ] - Bij doorverbinden spiraal geschikt voor ATEX zone 20	- Verkupferte und eingegossene Spirale - Wandstärke ca. 2,5 mm - Strömungsoptimiertes Profil - Antistatisch [R<10GΩ] - Beidseitige erdung der Spirale geeignet für ATEX Zone 20	- Wall thickness ca. 2,5 mm - Copperized steel and specially embedded torsion resistant spiral - Flow optimized profile - Antistatic [R<10GΩ] - With spiral to earth suitable for ATEX zone 20

Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. mm	Vacuüm Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m	Werkdruk Betriebsdruck Work. press. Bar
50.0		125.0	0.94	1.04	
75.0		190.0	0.90	1.80	
100.0		250.0	0.87	2.80	
125.0		315.0	0.87	4.09	
150.0		450.0	0.82	4.53	

Normen / Standards

Temperatuurbereik (Zie medium)
Temperatuurbereich (siehe Medium)
Temperature range (see media)
-40 °C +90 °C

Werkdruk Barstdruk
Betriebsdruck Platzdruck
Working pressure Burst pressure
1.5 - 4 bar bar

Markering / Markierung / Branding:
BATCH NUMBER

Lengten / Längen / Lengths
10 / 15 m
Kan per diameter verschillen / Kann je nach
Durchmesser variieren / Can vary per
diameter



-2024-

